

natural timber

ON RECEIPT OF YOUR FURNITURE FOLLOW THIS PROCEDURE:

1. shake the PRONATURE PLANT SOAP well and dilute it 1:5 with water
2. ensure furniture is free of dirt.
3. apply the dilute solution with a cloth to the surface and end grain and allow to penetrate and dry.
4. scour lightly with a scotchbrite scouring pad to render smooth.

NOTE - the early application of this oil rich plant soap helps prevent premature cracking. repeat this process as frequently as you like to help nurture the timber.

weathered timber

maintenance

4 x a year

wet the wood.

- scrub with scotch brite pads in the direction of the grain.
wash off the dirt and loose wood pulp residue.
dilute PRONATURE PLANT SOAP 1:5 with water.
apply to the surface and scrub in direction of grain.
agitate areas with severe marks with scotchbrite scourer.
1. rinse off and allow to dry.
 2. lightly scour surface with a dry scotchbrite scourer.

commercial situations i.e. restaurants etc.

natural timber tables will acquire oil marks from food and drink spillage.


1. dilute PRONATURE PLANT SOAP 1:5 with water.
2. wipe surfaces with a cloth and dilute solution between sittings.

oiled timber

maintenance

approx. 1 x a year.

1. scour lightly with scotch brite scourers in direction of grain to remove old oil and wipe surface clean of loose dirt.
2. apply PRONATURE OUTDOOR OIL lightly with a soft lint free cloth or brush.
3. **IMPORTANT REMOVE ANY EXCESS OIL WITH A DRY CLOTH AFTER APPROX. 15 MIN.**



rust metal

maintenance

1x a year (or when signs of dry, flaking rust)

1. scour frames with scotch brite pads to remove loose rust and brush clean.
2. apply PRONATURE WAX to the metal frame with a cloth and rub dry
3. **NOTE - THE WAX IS NOT FOR USE ON TIMBER**
4. **OIL** the articulating parts of the chairs and exercise the folding action 2 x a year



galvanised metal

NOTE - furniture in close proximity to the sea will show a formation of powdery white crystals as the zinc galvanised metal oxidises.

build up of this residue will be difficult to remove.

maintenance

washing 1x year

1. remove this residue in early stages with a high pressure hose or scour manually with scotchbrite pad and water
2. **OIL** the articulating parts of the chairs and exercise the folding action 2 x a year.



stone surfaces

maintenance

1. wipe up spillages promptly - always clean the table surface after meals with a damp cloth.
2. wash the stone often with WATER OR very dilute PRONATURE PLANT SOAP. **DO NOT** use harsh scouring cleaning materials or strong detergents.
3. apply BELLINZONI SPRAY POLISH sparingly but regularly with a soft cloth.

frequency: domestic - minimum 1 x a month

commercial minimum 1 x a week

further info and care

can be found on our website <http://hopegf.com>. all maintenance products can be purchased from the hope showroom, selected hardware stores or from our website.

showroom: 136 lower main rd, observatory | 021 448 7485 | info@hopegf.com

